




CRYSTAL

Technical Specifications

| | |
|--|--|
| Construction: Multi-level Loop | Standard Backing: EcoAce-Bac® |
| Fiber: Voxflor® Certified Nylon | Tile Size: Hexagons – 50cm*43.3cm |
| Gauge: 1/10” | Pile Weight: 17 OZ/yd² |
| Stitches: 10 per inch | Total Thickness: 6.5 ± 0.5 mm |
| Area per carton: 3.24m² | Piece per carton: 20 pieces |
| Traffic Classification: Commercial - Heavy Duty | Anti-microbial: Ultra Fresh (Available) |
| Average Pile Height: 4.0 ± 0.5 mm | |



Installation Methods



Random (Hexagon)

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
|  Declare. |  |  |  |  |  |  |  |  |
| Certificate Of Declare | Certificate Of Cradle To Cradle | Certificate Of SGLS | Certificate Of EPD | Certificate Of CRI | | | | |
| DOWNLOAD | DOWNLOAD | DOWNLOAD | DOWNLOAD | DOWNLOAD | | | | |

Performance Specifications

| | Test Code | Standard | Test Result |
|-------------------------------|------------------|----------------------------|---------------|
| Flammability Tests | | | |
| Radiant Panel | ASTM E 648 | ≥.45 watt/cm² | Class I |
| Methenamine Pill | ASTM D2859 | 7 out of 8 | 8 |
| Smoke Density | ASTM E 662 | ≤ 450 DMC | ≤ 450 |
| Stability | | | |
| Delamination | ASTM D3936 | ≥ 3.0 lbc/in | No Separation |
| Dimensional Stability | AACHEN | ≤ 0.2% | ≤ 0.2% |
| Tuft Bind | ASTM D1335 | ≥ 8.0 lbs | ≥ 8.0 lbs |
| Anti-Static | | | |
| Static Propensity | AATCC 134 | ≤ 3.5 kV | ≤ 3.5 kV |
| Colour Fastness | | | |
| Light | AATCC 16 E | ≥ 4-5 | 4-5 |
| Rubbing/Crocking | AATCC 165 | ≥ 4-5 | 4-5 |
| Wear Tests | | | |
| Castor Chair | BS EN 985 | r ≥ 2.4 | r = 2.8 |
| Hexapod Drum | ASTM D5252 | ≥ 3-4 | 3 |
| Generic Tests | | | |
| Nylon Carpet with EcoAce-Bac® | GLP No. : 100231 | | Accredited |
| Acoustic-Nylon | BS EN ISO 354 | Absorption Coefficient-NRC | aw =0.15(H) |

Warranty

Lifetime Commercial Limited **Warranty** [DOWNLOAD](#)

Additional Information

- VOXFLOOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

Additional Files

| | |
|--------------------------------|-------------------------------|
| Installation Guidelines | Maintenance Guidelines |
| DOWNLOAD | DOWNLOAD |






PRISM

Technical Specifications

| | |
|--|--|
| Construction: Level Loop | Standard Backing: EcoAce-Bac® |
| Fiber: Voxflor® Certified Nylon | Tile Size: Hexagons – 50cm*43.3cm |
| Gauge: 1/10” | Pile Weight: 20 OZ/yd² |
| Stitches: 10 per inch | Total Thickness: 5.5 ± 0.5 mm |
| Area per carton: 3.24m² | Piece per carton: 20 pieces |
| Traffic Classification: Commercial - Heavy Duty | Anti-microbial: Ultra Fresh (Available) |
| Average Pile Height: 3.0 ± 0.5 mm | |






Installation Methods



Random (Hexagon)

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications

| | | | | | |
|--|---|---|---|---|---|
|  |  |  |  |  |  |
|  |  |  |  |  | |
| Certificate Of Declare | Certificate Of Cradle To Cradle | Certificate Of SGLS | Certificate Of EPD | Certificate Of CRI | |
| DOWNLOAD | DOWNLOAD | DOWNLOAD | DOWNLOAD | DOWNLOAD | |

Performance Specifications

| | Test Code | Standard | Test Result |
|-------------------------------|------------------|----------------------------|---------------|
| Flammability Tests | | | |
| Radiant Panel | ASTM E 648 | ≥.45 watt/cm² | Class I |
| Methenamine Pill | ASTM D2859 | 7 out of 8 | 8 |
| Smoke Density | ASTM E 662 | ≤ 450 DMC | ≤ 450 |
| Stability | | | |
| Delamination | ASTM D3936 | ≥ 3.0 lbc/in | No Separation |
| Dimensional Stability | AACHEN | ≤ 0.2% | ≤ 0.2% |
| Tuft Bind | ASTM D1335 | ≥ 8.0 lbs | ≥ 8.0 lbs |
| Anti-Static | | | |
| Static Propensity | AATCC 134 | ≤ 3.5 kV | ≤ 3.5 kV |
| Colour Fastness | | | |
| Light | AATCC 16 E | ≥ 4-5 | 4-5 |
| Rubbing/Crocking | AATCC 165 | ≥ 4-5 | 4-5 |
| Wear Tests | | | |
| Castor Chair | BS EN 985 | r ≥ 2.4 | r = 2.8 |
| Hexapod Drum | ASTM D5252 | ≥ 3-4 | 3 |
| Generic Tests | | | |
| Nylon Carpet with EcoAce-Bac® | GLP No. : 100231 | | Accredited |
| Acoustic-Nylon | BS EN ISO 354 | Absorption Coefficient-NRC | aw =0.15(H) |

Warranty

Lifetime Commercial Limited Warranty [DOWNLOAD](#)

Additional Information

- VOXFLOOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

Additional Files

| | |
|--------------------------|--------------------------|
| Installation Guidelines | Maintenance Guidelines |
| DOWNLOAD | DOWNLOAD |

