




# BASALT CANYON

## NORTHERN EDGE COLLECTION


### Technical Specifications

<b>Construction:</b> Multi-level Loop	<b>Standard Backing:</b> EcoAce-Bac® Pro
<b>Fiber:</b> ECONYL® Regenerated Nylon by Aquafil	<b>Tile Size:</b> 25 x 100 cm
<b>Gauge:</b> 1/10”	<b>Pile Weight:</b> 28 OZ/yd²
<b>Stitches:</b> 10 per inch	<b>Total Thickness:</b> 8.5 ± 0.5 mm <b>Piece per carton:</b> 20 pieces
<b>Area per carton:</b> 5m²	<b>Anti-microbial:</b> Ultra Fresh (Available)
<b>Traffic Classification:</b> Commercial - Heavy Duty	
<b>Average Pile Height:</b> 4.5 ± 0.5 mm	

### Installation Methods



Ashlar



Herringbone

\*\*These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

### Certifications

 <b>Declare.</b>	 	 		 
Certificate Of Declare	Certificate Of Cradle To Cradle	Certificate Of SGLS	Certificate Of EPD	Certificate Of CRI
<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>

### Performance Specifications

	Test Code	Standard	Test Result
<b>Flammability Tests</b>			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
<b>Stability</b>			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
<b>Anti-Static</b>			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
<b>Colour Fastness</b>			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
<b>Wear Tests</b>			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
<b>Generic Tests</b>			
Nylon Carpet with EcoAce-Bac®	GLP No. : 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

### Warranty

**Lifetime Commercial** Limited Warranty [DOWNLOAD](#)

### Additional Information

- VOXFLOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

### Additional Files

<b>Installation Guidelines</b>	<b>Maintenance Guidelines</b>
<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>








# DIAMOND BEACH

## NORTHERN EDGE COLLECTION


### Technical Specifications

<b>Construction:</b> Multi-level Loop	<b>Standard Backing:</b> EcoAce-Bac® Pro
<b>Fiber:</b> ECONYL® Regenerated Nylon by Aquafil	<b>Tile Size:</b> 25 x 100 cm
<b>Gauge:</b> 1/10”	<b>Pile Weight:</b> 28 OZ/yd²
<b>Stitches:</b> 10 per inch	<b>Total Thickness:</b> 8.5 ± 0.5 mm <b>Piece</b>
<b>Area per carton:</b> 5m²	<b>per carton:</b> 20 pieces
<b>Traffic Classification:</b> Commercial - Heavy Duty	<b>Anti-microbial:</b> Ultra Fresh (Available)
<b>Average Pile Height:</b> 4.5 ± 0.5 mm	

### Installation Methods



Ashlar



Herringbone

\*\*These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

### Certifications

					
					
Certificate Of Declare	Certificate Of Cradle To Cradle	Certificate Of SGLS	Certificate Of EPD	Certificate Of CRI	
<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>	

### Performance Specifications

	Test Code	Standard	Test Result
<b>Flammability Tests</b>			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
<b>Stability</b>			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
<b>Anti-Static</b>			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
<b>Colour Fastness</b>			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
<b>Wear Tests</b>			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
<b>Generic Tests</b>			
Nylon Carpet with EcoAce-Bac®	GLP No. : 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

### Warranty

Lifetime Commercial Limited Warranty [DOWNLOAD](#)

### Additional Information

- VOXFLOr uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

### Additional Files

Installation Guidelines	Maintenance Guidelines
<a href="#">DOWNLOAD</a>	<a href="#">DOWNLOAD</a>

